



SYNOTag™ | **Passive**

SM9966XX 13.56 MHz RFID Reader

Passive 13.56 MHz RFID wall mount or desktop read only for ISO/IEC 15693 (I Code) RFID wristbands, cards and other tags. Suitable for applications where a read distance of up to 50 cm is required.

Features

- Reads ISO/IEC 15693 RFID tags
- Anticollision: Reads 30-50 tags per second
- 8 bits reader address supports networked readers
- RF output: 1 W
- Power supply: 12V DC
- Operating temperature: -25 to 60 degrees Celsius
- Storage temperature: -25 to 80 degrees Celsius
- Humidity: 5-95% RH
- Dimensions: 448.9 mm x 320.49 mm
- RS 232, RS 485 or USB interface available

Applications

- RFID Door Access Control
- RFID Access Card Reader
- RFID Parking Lot Access Control
- RFID POS Payment Systems
- RFID Door Security Systems



Product Warranty: SYNOMETRIX offers a standard 1 year repair or replace warranty from date of shipping on all products found to have a defect that results from manufacturing.

Visit us at www.synometrix.com or email us at info@synometrix.com

SYNOTag™ | **RFID**

For further information please contact:
John Hannon, Managing Director
SYNOMETRIX | **Asia Pacific** Taipei, Taiwan
IDD: +886 2 2758 1279