

SM-215 Waterproof RFID Seal Tags



SYNO Tag | RFID™

SM-215xx Seal with RFID Tag

Passive 125 KHz or 13.56 MHz RFID tags used as seals for meters of all types. Waterproof ABS makes these tags also suitable for outdoors or applications where a waterproof tag in this form-factor is desired. Functions like a regular meter seal with an RFID Tag attached for tracking and meter management. RFID Tag operates even if seal is tampered with or broken.

Applications

- RFID Taxi Bus or Truck Meter Seal Tag
- RFID Gas Meter Seal Tag
- RFID Electric Meter Seal Tag
- RFID Water Meter Seal Tag
- RFID Container Seal Tag

Specifications

- Reading Distance: 40 mm with GK 4001 Chip and EM 9917 Reader
- Operating Temperature: -40 to 70C
- Storage Temperature: -40 to 80C
- Material: ABS
- Waterproof

Available IC's

- EM 4102 (125 KHz, 64 bit, R/O)
- Hitag 1 (125 KHz, 2048 bit, R/W)
- Hitag 2 (125 KHz, 256 bit, R/W)
- I-Code (13.56 MHz, 512 bit, R/W, ISO 15693 & ISO/IEC 15693)

GPS | RFID | BIOMETRICS | INDUSTRIAL HANDHELD | BUY DIRECT



Visit us at www.synometrix.com or email us at info@synometrix.com

For further information please contact:

John Hannon, Managing Director

SYNOMETRIX | Asia Pacific Taipei, Taiwan

IDD: +886 2 2758 1279