



## **SYNO**Tag™ | **Passive**

### **SM-215xx Seal with RFID Tag**

Passive 125 KHz or 13.56 MHz RFID tags used as seals for meters of all types with reading distance up to 40 mm and operating temperature of -40 to 70C. Functions like a regular meter seal with an RFID Tag attached for tracking and meter management. RFID Tag operates even if seal is tampered with or broken.

### **Applications**

- RFID Taxi Bus or Truck Meter Seal Tag
- RFID Gas Meter Seal Tag
- RFID Electric Meter Seal Tag
- RFID Water Meter Seal Tag
- RFID Container Seal Tag

### **Available IC's**

- H4102 (125 KHz, 64 bit, R/O)
- Hitag 1 (125 KHz, 2048 bit, R/W)
- Hitag 2 (125 KHz, 256 bit, R/W)
- I-Code (13.56 MHz, 512 bit, R/W, ISO 15693 & ISO/IEC 15693)



**Product Warranty:** SYNOMETRIX offers a standard 1 year repair or replace warranty from date of shipping on all products found to have a defect that results from manufacturing.

## **SM-215 RFID Seal Tag**

Visit us at [www.synometrix.com](http://www.synometrix.com) or email us at [info@synometrix.com](mailto:info@synometrix.com)

# **SYNO**Tag™ | **RFID**

For further information please contact:  
John Hannon, Managing Director  
SYNOMETRIX | **Asia Pacific** Taipei, Taiwan  
IDD: +886 2 2758 1279