

SM-8866 Re-usable RFID Bracelet



SYNOTag | RFID™

SM-8866 Plastic RFID Bracelets

Waterproof 125 KHz and 13.56 MHz Passive RFID bracelets made of PC with operating temperature range of -40 C ~ 80 C. IC and wristband components are assembled separately to allow for upgrade to optional wristbands. Suited for close proximity (Up to 60 mm) RFID applications such as in office, building, warehouse and production line RFID access control.


Part Numbers

- Black: SM-8861BK
- Blue: SM-8861BU
- Green: SM-8861GE
- Yellow: SM-8861Y
- Purple: SM-8861P
- Red: SM-8861R

Available IC's

- GK4001 (125 KHz, 64bit, R/O)
- H4102 (125 KHz, 64 bit, R/O)
- Temic e5557 (125 KHz, 256 bit, R/W)
- I-Code (13.56 MHz, 512 bit, R/W, ISO 15693 & ISO/IEC 15693)
- Mifare 1 S50 (13.56 MHz, 1K Byte, R/W, ISO 14443 A)

Dimensions



GPS | RFID | BIOMETRICS | INDUSTRIAL HANDHELD | BUY DIRECT



Visit us at www.synometrix.com or email us at info@synometrix.com

For further information please contact:
John Hannon, Managing Director
SYNOMETRIX | Asia Pacific Taipei, Taiwan
IDD: +886 2 2758 1279