



## **SYNOtag™ | Passive**

### **SM-8869 RFID Bracelet**

125 KHz and 13.56 MHz Passive RFID bracelets made of PC with operating temperature range of -40 C ~ 80 C. Suited for close proximity (Up to 80 mm) RFID applications such as in office, building, warehouse and production line RFID access control.

#### **Available IC's**

- ▶ GK4001 (125 KHz, 64bit, R/O)
- ▶ H4102 (125 KHz, 64 bit, R/O)
- ▶ Temic e5557 (125 KHz, 256 bit, R/W)
- ▶ I-Code (13.56 MHz, 512 bit, R/W, ISO 15693 & ISO/IEC 15693)
- ▶ Mifare 1 S50 (13.56 MHz, 1K Byte, R/W, ISO 14443 A)



**Product Warranty:** SYNOMETRIX offers a standard 1 year repair or replace warranty from date of shipping on all products found to have a defect that results from manufacturing.

## **SM-8869 RFID Bracelet**

Visit us at [www.synometrix.com](http://www.synometrix.com) or email us at [info@synometrix.com](mailto:info@synometrix.com)

# **SYNOtag™ | RFID**

For further information please contact:  
John Hannon, Managing Director  
SYNOMETRIX | **Asia Pacific** Taipei, Taiwan  
IDD: +886 2 2758 1279