



Specifications

Electronic

- Modulation: Uplink/Downlink GFSK
- Communication Rate: Uplink/Downlink 1000kbit/s
- Frequency: 2.4 - 2.4835 GHz
- RF power output: -20dBm ~ -5dBm
- Sensitivity: -90dBm
- Bit Error Rate: 10⁻⁶
- EMI: 10V/m 0.1~1000 MHz AM electromagnetic wave
- Tag transmits signal to reader every 300ms - 500 ms

Environmental

- Temperature: -30 to 70C (Operating) -40 to 80C (Storage)
- Humidity: 100% Non-condensing
- Vibration & Shock: 10~2000 Hz 15g 3 axial
- Anti-electromagnetism: 10V/m 0.1~1000 MHz
- Battery Life: 3.0V lithium cell 6-8 years (10 years optional)
- Free Drop: 1M Concrete floor, twice per side
- Dimensions: 59mm x 34mm x 14mm
- Water resistant (not waterproof)

SMPK-101 Active RFID Tag

SYNOTag™ | **RFID**

SYNOTag | **Active**™

SMPK-101-R/O 2.4 GHz Active RFID Tag

2.4 GHz active RFID read only tag with read range of up to 80 meters when used with 2.45 GHz active RFID readers. Suited for any vehicle access control, vehicle toll collection, RFID asset tracking, manufacturing, personnel tracking and building access control applications.



Product Warranty: SYNO METRIX offers a standard 1 year repair or replace warranty from date of shipping on all products found to have a defect that results from manufacturing.

Visit us at www.synometrix.com or email us at info@synometrix.com

For further information please contact:
John Hannon, Managing Director
SYNO METRIX | **Asia Pacific** Taipei, Taiwan
IDD: +886 2 2758 1279