

Tag XXX RFID Tags



SYNOTag | RFID™

Waterproof RFID Tokens and Tags

Passive 125 KHz or 13.56 MHz waterproof RFID token tags. Suitable for applications where a waterproof tag in this form-factor is desired with read distance of up to 150 mm (depends on reader).

<u>Tag Type</u>	<u>Material</u>	<u>Dimensions</u>	<u>Thickness</u>	<u>Read Distance</u>
Tag 301	ABS	Ø 30mm Hole 5mm	3 mm	50 mm
Tag 302	ABS	Ø 30mm Hole 5mm	4 mm	50 mm
Tag 401	ABS	Ø 40mm Hole 5mm	4.2 mm	80 mm
Tag 501	ABS	Ø 52mm Hole 5mm	8 mm	150 mm

- Read distances calculated using GK4001 IC with EM 9917 Reader
- Operating temperatures: -40C ~ +70C

Available IC's

- GK4001 (125 KHz, 64bit, R/O)
- I-Code (13.56 MHz, 512 bit, R/W, ISO 15693 & ISO/IEC 15693)
- Mifare 1 S50 (13.56 MHz, 1K Byte, R/W, ISO 14443 A)

GPS | RFID | BIOMETRICS | INDUSTRIAL HANDHELD | BUY DIRECT



Visit us at www.synometrix.com or email us at info@synometrix.com

For further information please contact:
John Hannon, Managing Director
SYNO METRIX | Asia Pacific Taipei, Taiwan
 IDD: +886 2 2758 1279