



Specification

- ↳ Dimensions: Inner Diameter - 15.5mm
- ↳ Dimensions: Outer Diameter - 19.8mm
- ↳ Dimensions: Length - 59.6mm
- ↳ Material: Silicone
- ↳ Colours: Blue/Yellow/Purple/Green/White/Pink

SYNOtag™ | Passive

SM-208 Test Tube RFID Tags

Waterproof silicone 13.56 MHz RFID tags for use with test tubes or in other applications where a slip-on RFID tag is required. Operating temperature of -40C ~ +100C and read distance of up to 50 mm (depends on reader).

Available IC's

- ↳ H4102 (125 KHz, 64 bit, R/O)
- ↳ I-Code (13.56 MHz, 512 bit, R/W, ISO/IEC 15693)
- ↳ Mifare 1 S50 (13.56 MHz, 1K Byte, R/W, ISO 14443 A)



Product Warranty: SYNOMETRIX offers a standard 1 year repair or replace warranty from date of shipping on all products found to have a defect that results from manufacturing.

SM-208 RFID Test Tube Tag

SYNOtag™ | RFID

Visit us at www.synometrix.com or email us at info@synometrix.com

For further information please contact:
John Hannon, Managing Director
SYNOMETRIX | **Asia Pacific** Taipei, Taiwan
IDD: +886 2 2758 1279