



SYNO**Tag**™ | UHF

UHF Labels | Up to 5 Meter Read Range

860~960 MHz EPC Global Class 1 Gen 2 ISO 18000-6C UHF smart labels suited for supply chain and logistics, document and asset tracking applications.

Features

- ▶ Operating frequency: 860~960 MHz
- ▶ Standard: EPC Global Class 1 Gen 2 ISO 18000-6C
- ▶ EPC Memory: 96 bits
- ▶ Protocol Control Bits: 16 bits
- ▶ Access Code: 32 bits
- ▶ Kill Code: 32 bits
- ▶ Write endurance: 10,000 cycles
- ▶ Label material: Paper
- ▶ Storage temperature: -5°C to 60°C

<u>Part Number</u>	<u>Label Size</u>	<u>Read Range</u>
VAT1810	10x18mm	300-500mm
V3623	8x20mm	300mm
U208	23x36mm	1.5 Meter
U958	8x95mm	5.5 Meter



Product Warranty: SYNOMETRIX offers a standard 1 year repair or replace warranty from date of shipping on all products found to have a defect that results from manufacturing.

UHF Smart Labels

SYNO**Tag**™ | RFID

Visit us at www.synometrix.com or email us at info@synometrix.com

For further information please contact:
John Hannon, Managing Director
SYNOMETRIX | **Asia Pacific** Taipei, Taiwan
IDD: +886 2 2758 1279