



# SM-U1157 RFID Windshield Tag -Tamperproof



UHF windshield tag for RFID vehicle access control and RFID parking management. Tag breaks when peeled and cannot be re-used. Tag dimensions 105x87mm with peel and stick backing and suited for use in temperatures up to 80C. Read distance up to 6 meters using Alien ALR 9800 reader.

## SYNOTAG

| SPECIFICATIONS                            |  |
|---|--|
| Logo Printing: Yes                        | Dimensions: 105x87mm   |
| Memory:                                   | » 32 bit Kill Passwords<br>» 32 bit Access Passwords<br>» Typical 96 bits EPC Number23 |
| RoHS: Yes                                 | IC Type: EPC Global C1G2 ISO 18000-6C  |
| Storage temperature: -20 to +80 degrees C | Operating temperature: -20 to +80 degrees C  |
| APPLICATIONS                              |  |
| RFID Toll Collection                      | RFID Vehicle Tracking  |
| RFID Vehicle Identification               | RFID Parking Management  |
| RFID Vehicle Access Control               | RFID Gated Community Access Control  |
| RFID Car Wash Vehicle Access Control      |  |



SYNOMETRIX offers a standard 1 year repair or replace warranty from date of shipping on products found to have a defect that results from manufacturing.